



IT.	DESCRIPTION	MATERIAL
1	BODY	ASTM A216 GR. WCB
2	SEAT RING	ASTM A105 + STELLITE
3	DISC	ASTM A216 WCB/13CR.
4	DISC NUT	ASTM A194 GR. 2H
5	HINGE	ASTM A216 GR. WCB
6	HINGE PIN	ASTM A182 GR. F6a
7	YOKE	ASTM A216 GR. WCB
8	COVER	ASTM A216 GR. WCB
9	GASKET	316 + GRAPHITE
10	COVER BOLT	ASTM A193 GR. B7
11	COVER NUT	ASTM A194 GR. 2H
12	HINGE BOLT	ASTM A193 GR. B7

SIZE	L	N	H	End Flange					
				D	Bolt Hole			g	b
					K	No.	d		
2"	10.5	2	7.68	6.5	5	8	0.75	3.625	0.88
50mm	267	51	195	165	127	8	20	92	22.5

STANDARDS	
Design	API 6D, ANSI B 16.34
Pressure - Temp. Rating	ANSI B16.34
Face to Face Dimension	ANSI B16.10
Connection	ANSI B16.5
Test & Inspection	API 598

CUSTOMER:
P.O. NUMBER:
TAG NUMBER:
JOB NUMBER:
BB/TRIM: A216 GR. WCB / 13 CR.

BONNEY FORGE
 U.S. ROUTE 522 SOUTH
 P.O. BOX 330
 MOUNT UNION, PA 17066

ISO 9001
 Certificate Number: 30116

**SWING CHECK VALVE
 CAST STEEL BOLTED BONNET
 ANSI CLASS 300 SIZE 2"**

REV	DESCRIPTION	DATE	BY	DR.	DATE	DRAWING NO.	REV.
	REVISIONS			BSG	11-9-99	3-61-RF	0
				GLW	NONE		