

IT.	DESCRIPTION	MATERIAL
1	BODY	ASTM A216 Gr. WCB
2	SEAT RING	ASTM A105 + Stellite
3	DISC	ASTM A216 WCB/13Cr
4	DISC NUT	ASTM A194 Gr. 2H
5	HINGE	ASTM A216 Gr. WCB
6	HINGE PIN	ASTM A182 Gr. F6a
7	YOKE	ASTM A216 Gr. WCB
8	COVER	ASTM A216 Gr. WCB
9	EYEBOLT	ASTM A105
10	GASKET	GRAPHITE or OPTION
11	COVER BOLT	ASTM A193 Gr. B7
12	COVER NUT	ASTM A194 Gr. 2H
13	HINGE BOLT	ASTM A193 Gr. B7

SIZE	L	N	H
8"	19.5	8.0	14.37
200mm	495	203	365


STANDARDS	
Design	API 6D, ANSI B 16.34
Pressure - Temp. Rating	ANSI B16.34
Face to Face Dimension	ANSI B16.10
Connection	ANSI B16.25
Test & Inspection	API 598

<b>CUSTOMER:</b>
<b>P.O. NUMBER:</b>
<b>TAG NUMBER:</b>
<b>JOB NUMBER:</b>
<b>BB/TRIM:</b> ASTM A216 Gr. WCB / 13 CR.

B

**BONNEY FORGE**

U.S. ROUTE 522 SOUTH  
P.O. BOX 330  
MOUNT UNION, PA 17066



**ISO 9001**  
Certificate Number: 30116

**SWING CHECK VALVE (BW)  
CAST STEEL BOLTED BONNET  
ANSI CLASS 150 SIZE 8"**

REV	DESCRIPTION	DATE	BY	DR.	DATE	DRAWING NO.	REV.
	REVISIONS			BSG	5-22-00	1-61-BW	0
				GLW	NONE		