

IT.	DESCRIPTION	MATERIAL
1	RIVET	CARBON STEEL
2	NAME PLATE	ALUMINUM
3	B/B BOLTS	A193-B7M
4	B/B GASKET	F316L + GRAPHITE
5	HINGE	F316L
6	BONNET	A105
7	DISC	F316L
8	HINGE PIN	F316L
9	SEAT RING	F316L + STELLITE
10	DISC NUT	A194-GR.8
11	BODY	A105

- SMOOTH FINISH (125-250 AARH)
- SERRATED SPIRAL FINISH
- _____


VALVE SIZE	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2
DIMENSION								
A			4 1/4	4 5/8	5		6 1/2	8
B			2 15/16	2 15/16	3 3/8		4 5/16	4 15/16
C			3 1/2	3 7/8	4 1/4		5	6
D			1 3/8	1 11/16	2		2 7/8	3 5/8
E			.378	.551	.689		1.161	1.441
F			7/16	1/2	5/8		11/16	13/16
ITEM#								
APPROX. WT.			4 3/4	6 3/4	9 3/4		18 1/4	28 3/4

CUSTOMER: _____
P.O. NUMBER: _____
TAG NUMBER: _____
JOB NUMBER: _____
BB/TRIM: A105 / F316L

B

BONNEY FORGE

U.S. ROUTE 522 SOUTH
P.O. BOX 330
MOUNT UNION, PA 17066



ISO 9001
Certificate Number: 30116

**SWING CHECK VALVE
INTEGRAL RF FLANGED ENDS
1/2" to 2" CL.150# RED. BORE**

REV	DESCRIPTION	DATE	BY	DR.	DATE	DRAWING NO.	REV.
	REVISIONS			BSG	12-17-98	L1-63-RF	0
				GW	NONE		