


# A Series Forged Brass CSA Gas Ball Valves

## 326



Forged 2 piece construction  
Flare x Flare  
Smooth, quarter turn operation  
May be used with water 400 PSI  
Seals at high and low pressure -  
ideal for testing installations  
For use with natural, manufactured,  
liquefied petroleum &  
LP gas-air mixtures to  
ANSI Z21.15, CSA 9.1 (1/2 PSIG)  
ASME B16.44,  
CGA CR91-002 (2 & 5 PSIG)  
-40° to 125°F

6.2



### NAME / MATERIAL

1. Handle / Aluminum ASTM B85-A03840
2. Screw / Steel ASTM 36 Zinc Plated
3. Stem-O-Ring / NBR 70SH
4. Stem-O-Ring / Viton
5. Stem / Brass ASTM B124-C37700
6. Seats / PTFE
7. Body / Brass ASTM B283-C37700
8. Ball / Chromium Plated Brass ASTM B124-37700
9. Body-Cap / Brass ASTM B283-C37700

### D I M E N S I O N S

size (in.)	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{5}{8}$
A	59.9	66.5	79.4
mm/in	2.34	2.59	3.10
B	37.8	37.8	37.8
mm/in	1.47	1.47	1.47
C	32.3	32.3	36.8
mm/in	1.26	1.26	1.44
D	7.14	10.3	12.7
mm/in	0.28	0.40	0.49
E size	$\frac{5}{8}$ x 18UNF	$\frac{3}{4}$ x 16UNF	$\frac{7}{8}$ x 14UNF
F	15.7	19.0	22.4
mm/in	0.61	0.74	0.87
Weight	0.3	0.3	0.5
lb/kg	0.40	0.40	0.62