


B Series Forged Brass PEX X Solder Ball Valve

B-2PEX



- Forged 2 piece construction
- Reduced port
- B16.22 solder end X
ASTM F1807-08 PEX end (CXPEX)
- Blowout-proof stem
- Chrome plated ball
- O ring stem seals
- 400 WOG
- NSF-61-9 certified**



P A R T / M A T E R I A L

1. Handle / Steel ASTM A36
2. Lever Screw / Steel ASTM A36
3. Stem / Brass ASTM B124-C37700
4. O Ring / NBR
5. Ball / Brass ASTM B124-C37700 Chrome Plated
6. Cap / Brass B283-C37700
7. Body / Brass B283-C37700
8. Seat / PTFE

***NOTE:**

- 1) The safe working pressure-temperature rating for a solder joint piping system is dependent not only on valve seat rating but also on the limitation of the solder used for the joints. Refer to ANSI B16-22, Table I.1 for the Maximum recommended pressure-temperature ratings for solder joints.
- 2) Exercise caution during installation by applying heat away from the valve body. Excessive direct flame may damage body seats and seals.
- 3) The safe working pressure-temperature rating for this valve in a PEX piping system is dependent not only on the valve seat rating but also the limitations of the PEX pipe used. Refer to the CSA-B137 standard Table A1 below for these limits.

D I M E N S I O N S

size (in.)	A mm/in	B mm/in	C mm/in	D mm/in	E mm/in	F mm/in	CV	Weight lb/kg
1/2	54.1	26.2	39.9	8.9	12.0	16.0	7	0.243
	2.13	1.03	1.57	0.35	0.47	0.63		0.11
3/4	60.9	26.2	41.9	13.5	16.9	16.0	13	0.324
	2.40	1.03	1.65	0.53	0.67	0.63		0.15

**Table A1: Pressure Rating for PEX SDR9
Water Distribution Systems**

Rated Temperature °C / °F	Pressure Rating for Water KPA / (PSI)
23 / 73	1105 / (160)
82 / 180	690 / (100)
93 / 200	550 / (80)

