



DIMENSIONS UNIT: mm

SIZE		a	d1	H	L	D	S	MASS (Kg)	Q'ty
mm	Inch								
100	4	NPT 4	100	302	140	160	130	11.2	



BODY MARKING

PROJECT:  
OWNER:  
ENGINEER:  
CONTRACTOR:

## TOYO Figure 206

NOTE:  
\* DR Alloy denotes Patented Dezincification-Resistant Copper Alloy.

11	NAME PLATE	ALUMINIUM	
10	WHEEL NUT	A307-B	Zinc-Plated
9	HAND WHEEL	B85-SC114A	
8	GLAND PACKING	Non-asbestos packing	
7	GLAND	B16	
6	PACKING NUT	B283-C37700	
5	LOCK NUT	B16	
4	DISC	B62-C83600	
3	STEM	DR Alloy *	
2	BONNET	B62-C83600	
1	BODY	B62-C83600	

No.	PART	MATERIAL (ASTM)	NOTE
CONNECTION			
		ASME B1.20.1	<b>CLASS 125 CAST BRONZE SCREWED END GATE VALVE NON-RISING STEM, SOLID WEDGE DISC</b>
FACE TO FACE or END TO END		Toyo's Spec.	
TRIM DESIGNATION			

APP'D	TEST PRESSURE	VALVE CODE
CHK'D	SHELL SEAT	125E-BS-N NPT
CHK'D	HYDRO	FIG. No.
PREP'D	STATIC	206
SCALE	AIR	DRAWING No.
DATE		05AA6626-2C

REVISION					△				
MARK	DATE	PREP'D	CHK'D	APP'D	DESCRIPTION	△			
△						△			

**Toyo Valve Co., Ltd.**