


DIMENSIONS

UNIT: mm

SIZE		d	d1	H	L	D	S	MASS (kg)	Q'ty
mm	Inch								
65	2½	NPT 2½	63	201	90	110	86	2.73	
80	3	NPT 3	76	223	100	125	100	3.73	



BODY MARKING

PROJECT:  
OWNER:  
ENGINEER:  
CONTRACTOR:

# TOYO Figure 206

NOTE:

\* DR Alloy denotes Patented Dezincification-Resistant Copper Alloy.

11	NAME PLATE	ALUMINIUM	
10	WHEEL NUT	A307-B	Zinc-Plated
9	HAND WHEEL	B85-SC114A	
8	GLAND PACKING	Non-asbestos packing	
7	GLAND	B16	
6	PACKING NUT	B283-C37700	
5	LOCK NUT	B16	
4	DISC	B62-C83600	
3	STEM	DR Alloy *	
2	BONNET	B62-C83600	
1	BODY	B62-C83600	
No.	PART	MATERIAL (ASTM)	NOTE

CONNECTION		<b>CLASS 125</b> <b>CAST BRONZE</b> <b>SCREWED END GATE VALVE</b> <b>NON-RISING STEM, SOLID WEDGE DISC</b>
ASME B1.20.1		
FACE TO FACE or END TO END		
Toyo's Spec.		
TRIM DESIGNATION		

APP'D	TEST PRESSURE	VALVE CODE
<i>K. Kalyapadi</i>	SHELL SEAT	125E-BS-N NPT
CHK'D	HYDRO 2.1 MPa	FIG. No.
<i>N. Patel</i>	STATIC 300 PSI	206
PREP'D	AIR 0.6 MPa	DRAWING No.
<i>H. Komatsu</i>	80 PSI	05AA6626-1C
SCALE	NON	
DATE	OCT. 2, '06	

REVISION					△			
MARK	DATE	PREP'D	CHK'D	APP'D	DESCRIPTION	△		
△						△		



**Toyo Valve Co., Ltd.**