



Tubing & Casing Coupling API

Pony Rods

UPCO C Carbon – Medium Strength API C
 UPCO CD Carbon – High Strength API Carbon D
 UPCO AD Medium Alloy – High Strength API Alloy D
 UPCO KD High Alloy – High Strength API Special D
 UPCO K High Alloy – Medium Strength API K
 UPCO HS High Alloy – Extra High Strength

Sucker Rod Couplings

For Pin Sizes 5/8", 3/4", 7/8", 1" & 1 1/8"
 Full Size, Slim Hole or Special Dia.
 Type T or Spray Metal

UPCO Pup Joints

API Monogrammed Pup Joints
 Meet Standard Test Pressures of:
 J-55 2 3/8" 7,000 PSI N-80 2 3/8"
 10,000 PSI
 J-55 2 7/8" 6,600 PSI N-80 2 7/8"
 9,700 PSI
 J-55 3 1/2" 6,400 PSI N-80 2 1/2"
 9,300 PSI
 Available in 2' Through 12' Lengths

Stuffing Box Packing

Valve Cups; Seating Cups;
 Fluid-Seal Rod Packing; Special "V" Packing; Stuffing Box Packing; Resistoil Rings; Type "B" Rings; Plunger Pump Packing; Compression Packing

Central Plastics LLC

Flange Insulation Kits
 1" thru 24" ANSI 150 Stock
 2" thru 12" ANSI 300 Stock
 2" thru 12" ANSI 600 Stock
 Cut Ring & Full Face Gaskets Available

Insulated Unions

3000# Hex Unions Stock
 3000# Handle Bar Unions Stock
 Dielectric Unions Available

Tubing Couplings

1 1/4" thru 4 1/2" 8rd EUE
 J-55 – N-80 – L80 – other Grades Available
 Upset & Non-upset

Casing Couplings

4 1/2" Thru 13 3/8" in Stock
 8rd Short, 8rd Long, Buttress
 K-55 & N-80 Stock
 Other Grades Available From Factory



Pressure Gauges

2 1/2" Face and 4" Face Gauges,
 All Stainless Steel Glycerin Filled
 0 – 30 PSI thru 0 – 6000 PSI

Other Styles & Pressure Available

